

Helios I 06

The Helios family combines the state-of-the-art technology of Bartolini's infra-red burner with a wide, robust frame, specifically designed for ensuring functionality and easiness of use.



Technical features

The radiant unit is composed of three ceramic plates with three different powers which can be used separately to quickly heat the room. This is the ideal infra-red heater for those who love the warmth of "fire".

The combustion is in fact clearly visible and ensures a high irradiation capacity. It is fed by 15-kg, LPG cylinders. The four reinforced casters rotate 360° and ensure an easy movement in every direction and on any floor.



Helios I 06 cod. 314

BAR CODE: 8015937123144

| | | | |
|-----------------------------|--------------------------|-------------------|--------------------|
| Gas Data | Feeding | - | LPG |
| | Gas cylinder | [kg] | 15 |
| | Gas power delivered | [W] | 1400 - 2800 - 4200 |
| | Consumption | [g/h] | 300 |
| | Gas heatable volume | [m ³] | 120 |
| Electrical Data | Switching on | - | Piezoelectric |
| | Ventilation | - | - |
| | Thermo-ventilation | - | - |
| | Electric power delivered | [W] | - |
| | Electric heatable volume | [m ³] | - |
| Sizes and weights | Product size | [cm] | 43 x 42 x 78 |
| | Cylinder compart. size | [cm] | 32 x 38.5 x 70.5 |
| | Packaging size | [cm] | 44 x 36 x 82 |
| | Weight | [kg] | 13.6 |
| | Container 40 HC | no. | 542 |
| | Quantity 20 HC | no. | 350 |
| | EPAL size 15 pcs | [cm] | 120 x 82 x 235 |
| | No. of 40-foot pallets | no. | - |
| No. of pallets in the truck | no. | 32 | |

Safety and quality

1 - Bartolini's Analyser

This device constantly controls and analyses the air and stops the gas supply if the carbon dioxide level in the room exceeds 1.5%. Bartolini autonomously produces it by precision drilling on hard stones (rubies) and guarantees its high quality and operation through continuous tests during manufacturing and in laboratory.

2 - Thermocouple

Safety device which automatically stops the gas supply in case of accidental shut-down (air stream, etc.).

3 - Gas pipe and pressure controller

These certified, high-quality components are installed on all Bartolini products and ensure a suitable connection to the LPG cylinder.

